

FatTwin A+ Server AS -F1114S-RNTR

4U 8-node FatTwin with 2 2.5" NVMe/SATA + 2 2.5" SATA drives per node



More details here

Key Applications

Virtualization, Enterprise Applications, Hyperscale / Hyperconverged, HPC, Big Data, Data Center Enterprise Applications, Scale-Out Storage, Telco Data Center,

Key Features

- Eight **hot-pluggable** systems (nodes) in a 4U form factor. Each node supports the following;;
- Single AMD EPYC™ 7003/7002 Series Processor
(The latest AMD EPYC™ 7003 Series Processor with AMD 3D V-Cache™ Technology requires BIOS version 2.3 or newer);
- Up to 2TB ECC 3DS LRDIMM
up to DDR4-3200MHz; 8 DIMM slots;
- Expansion slots: 1 PCIe 4.0 x16 LP
1 PCIe 4.0 x16 AIOM slot;
- AIOM Network card
1 dedicated IPMI LAN port;
- 6 Hot-swap 2.5" drive bays
2 NVMe/SATA3, 4 SATA3 (optional NVMe with additional cables)
M.2 Interface: 4 SATA/PCIe 4.0 x4
M.2 Form Factor: 2242, 2260, 2280, 22110

Form Factor

4U Rackmount
Enclosure: 448 x 177 x 737mm (17.63" x 6.96" x 29")
Package: (28.3" x 15" x 42.4")

Processor

Single Socket SP3
AMD EPYC™ 7002/7003 Series Processors

System Memory

Slot Count: 8 DIMM slots
Max Memory (1DPC): Up to 2TB 3200MT/s ECC DDR4 RDIMM/LRDIMM

Drive Bays Configuration

Default: Total 6 bays

- 2 front hot-swap 2.5" NVMe/SATA drive bays
- 4 front hot-swap 2.5" NVMe*/SATA drive bays

(*NVMe support may require additional storage controller and/or cables, please see the optional parts list for details)
M.2: 4 M.2 PCIe 4.0 x4 SATA slots (M-key 2242/2260/2280/22110)

Expansion Slots

Default

- 1 PCIe 4.0 x16 LP slot
- 1 PCIe 4.0 x8 INTERNAL slot



On-Board Devices

Network Connectivity: Ethernet
IPMI: Support for Intelligent Platform Management Interface v.2.0
IPMI 2.0 with virtual media over LAN and KVM-over-LAN support

Input / Output

LAN: 1 RJ45 1 GbE Dedicated BMC LAN port
USB: 2 USB 3.0 ports (rear)
Video: 1 VGA port
TPM: 1 TPM header





System Cooling	Fans: Up to 3x 17.6K RPM middle 4cm Fan(s)
Power Supply	4x 2200W Redundant (2 + 2) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 256MB SPI Flash EEPROM
Management	Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); KVM with dedicated LAN ; IPMI 2.0; Watch Dog
PC Health Monitoring	CPU: Monitors for CPU Cores Fan: Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 200 lbs (90.71 kg) Net Weight: 150 lbs (68.04 kg) Available Color: Silver
Operating Environment	RoHS Compliant Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)
Motherboard	Super H12SSFR-AN6
Chassis	CSE-F424AS3-R2K20BP